

Wireless Remote Controls

PowerTouch P1000 Series

Takes a **Dip**
&
Keeps its **Zip**



Sealed «
500 Ft Range «
Rolling Codes «
Versatile «
Economic «
Mix N Match «

- » 2, 4 and 6 button transmitters can be matched with all receiver styles
- » All receivers will accept switched inputs
- » Customize the receiver to fit your application



Designed & Manufactured By:

TouchTronics, Inc.

57315 Nagy Drive
Elkhart, IN 46517

Ph: 1-800-294-2570
Fx: 1-574-293-1611

touchtronics@touchtronics.com
www.touchtronics.com



P1000 Series
Standard Unsealed
6 1/2" x 5 1/2"



P1200 Series
Standard Seal - Dust, Moisture
Super Seal - Hi Pressure Wash
9 1/4" x 5 1/4"



P1500 Series
Standard Unsealed
5 1/4" x 3"

System Specifications

P1000/P1200 Receivers

Range	- 300 Feet Typical - Up to 600 Feet
Output	- 4 Relays
Optional	- 7 Relays
Input	- 2 (+12v) A1 & A2
Optional	- 6 (+12v or Ground) B1 - B6
Frequency	- 433MHz
Codes	- Rolling Codes - Secure Encryption
Voltage	- 12VDC - 24VDC
Current	- 5 Amps Max per Output - 10 Amp Input - 30 Amp Input
Harness	- 9" Standard, 14 pin

System Specifications

P1500 Receiver

Range	- 300 Feet Typical - Up to 600 Feet
Output	- 1, 2 & 4 Relays
Input	- 2 (+12v)
Frequency	- 433MHz
Codes	- Rolling Codes - Secure Encryption
Voltage	- 12VDC - 24VDC
Current	- 5 Amps Max per Output - 10 Amp Input
Harness	- 9" Standard, 8 pin



TK & TF Series
Sealed
Transmitters

TM & TX Series
Un-Sealed
Transmitters



P1000-TX2
P1000-TX2S*

P1000-TX4
P1000-TX4S*

P1000-TX6

Battery	- All Transmitter Styles
	- Coin Style, Lithium, CR2032
	- 100,000 1-second pulses
	- 10 year shelf life

*S denotes On/Off Switch

Standard Antenna Options



Fixed Antenna

TNC Antenna

Optional Antennas for Increased Range



Phantom
Antenna

Glass Mount
Antenna

Bulk Head
Antenna

Designed & Manufactured By:

TouchTronics, Inc.

57315 Nagy Drive
Elkhart, IN 46517

Ph: 1-800-294-2570
Fx: 1-574-293-1611

touchtronics@touchtronics.com
www.touchtronics.com

Available Co-axial Cable:
2, 5, 14 & 29 Foot Lengths